

HCP Micro SG-2 Industrial computer



Procesor: 100MHz, 32-bit, Ajile

Opšte karakteristike:

Dimenzije: 135x128x45mm

Težina: 820g

Boja: Crna

Procesor: Intel Celeron 1037u Dual-Core 1.8GHz

Memorija: 4GB 1333MHz DDR3 SO-DIMM Memorija; 1 x

Memory Slot, podržava do 8 GB

Hard disk: 64 GB mSATA SSD; mSATA port; velikog kapaciteta

mSATA SSD is optional Onboard VGA: Intel HD Graphics

LAN: RJ – 45 port; Realtek RTL8111E 10/100/1000 Controller

Wireless: Opciono

Bluetooth: Opciono

Audio: Realtek ALC662 HD Audio

Potrošnja el.energije: 12W, max 23W

Chipset: Intel NM70

Konektori na prednjem panelu:

- 1 x taster za napajanje (Power LED)

- 1 x HDD LED

- 2 x USB2.0 priključak

- 1 x mikroskop priključak

- 1 x serijski priključak

Konektori na zadnjem panelu:

- 1 x 12V DC ulaz

- 1 x HDMI priključak

- 1 x VGA priključak

- 1 x RJ-45 priključak

- 1 x USB 2.0 priključak

- 1 x Zvucnik priključak

Operativni sistem: Bez operativnog sistema

Pakovanje podrazumeva: SG micro1, napajanje i utikac, držac, šrafovi, antene

Mehanički standard: NANO ITX industrijska matična ploča; 120mm x 120mm

Chipset: Intel NM70

Procesor: Intel Celeron Procesor 1037u (2M Cache, 1.80GHz Dual-Core); do 17 W TDP

Glavne karakteristike:

BIOS: AMI BIOS; 16MBit SPI BIOS

Memorija: One 204-pin DDR3 SDRAM Small Outline (SO-DIMM) socket Support DDR3 1333 MHz and DDR3 1600 MHz SO-DIMM; Support 8GB MAX

Grafika: Intel HD Graphics

Displej: VGA / HDMI/LVDS Dual Display; 1x HDMI (port), 1x VGA (pin), 1x LVDS (pin)

LAN: 1x Realtek RTL8111E 1000M

Audio: Realtek ALC662 HD Audio Decoding controller; 6

Channel Audio output; Line out + MIC IN Port

COM: 1x COM(RS232 port)

USB: 3x On-board USB 2.0; 1x Pin interface USB 2.0

Storage: 1x SATA 3.0 (6Gb/s); 1x Mini PCIE port

Interfejsi:

- 1x PCI Express Full-Mini Card connector (for mSATA SSD)

- 1x PCI Express Half-Mini Card connector (for WIFI and Bluetooth)

- 1x SATA power connector

- 1x SATA 3.0 connector (6Gb/s)

- 1x DDR3 SO-DIMM socket

- 1x Front panel header

- 1x 9 Pin VGA header

- 1x LVDS header (optional)

- 1x Front panel audio header

- 1x Front panel dual-port USB 2.0 header

Prednji panel:

- 1x Push button (With LED) for Power ON/OFF

- 2x USB 2.0 ports

- 1x Serial port

- 1x HDD LED

- 1x Mic in port

Zadnji panel:

- 1x DC in connector

- 1x HDMI port

- 1x VG(D-Sub) port

- 1x RJ45 1000M port

- 1x USB 2.0 port

- 1x Speaker out port

Napajanje: DC 12-19V

Radni uslovi: Radna temperatura -10š-60šC; operativna vlažnost 10%-90% relativne vlažnosti